



PlaceMakers Splash

SEND US A PHOTO OF YOUR PROJECT
AND RECEIVE A

\$50 PREZZY CARD*

*Terms & conditions apply.

Scan the QR Code to view
the PlaceMakers Splash
Installation Guide:



Flame retardant



Low maintenance



Easy to install



Cost effective



Seamless finish



Water resistant

PlaceMakers Splash



PRODUCT SKUS						
	750mm x 600mm	750mm x 900mm	750mm x 2100mm	750mm x 3100mm	2100mm x 1550mm	3100mm x 1550mm
Silver/Sand	5711244	5711243	5711220	5711222	5711219	5711221
Mint/Anthracite	5711246	5711245	5711224	5711226	5711223	5711225
Teal/Ash	5711248	5711247	5711228	5711230	5711227	5711229
Grey/Brushed Aluminium	5711250	5711249	5711232	5711234	5711231	5711233
Black/Sky	5711252	5711251	5711236	5711238	5711235	5711237
White/Red	5711254	5711253	5711240	5711242	5711239	5711241
Black/White Marble	3622098	3622090	3622096	3622097	3622134	3622133

What Is PlaceMakers Splash?

PlaceMakers Splash is a flame retardant aluminium composite splashback and wall panelling solution. It is the ideal alternative to glass, acrylic and porcelain tiles and can be used for residential and commercial applications.

Features & Benefits

- Cost effective
- Flame retardant
- Lightweight & durable
- Water resistant
- Low maintenance
- Suitable behind gas hobs
- Mirror like gloss & seamless finish
- Easy to install & fabricate

Typical Applications

- Kitchen Splashbacks
- Shower Linings
- Retail Fitouts
- Laundry Areas
- Feature Walls
- Wall Linings

Features	PlaceMakers Splash	Glass	Acrylic	Porcelain
Fire resistance	✓	✓	X	✓
DIY & easy to cut	✓	X	✓	X
Affordability	✓	X	✓	✓
Easy to install	✓	X	✓	X
Low maintenance	✓	✓	✓	X
Large panel	✓	X	✓	X

PlaceMakers Splash Range

Sheet Size:

600mm x 750mm, 900mm x 750mm, 2100mm x 750mm, 3100mm x 750mm, 2100mm x 1550mm & 3100mm x 1550mm

Colour Range:



PSP Aluminum Trims



Colours shown in this brochure are subject to limitation of commercial printing and may not necessarily represent the actual colour. It is highly recommended that an actual colour sample be requested before purchasing. Colour and gloss variations within the company's acceptable tolerances could occur between different production batches and shall be treated as acceptable. All visual inspection of panels sheets must be carried out from a two metre distance of the panel or panels sheets being placed vertically on or against a wall.

NOTE: Uncontrolled in printed format.

v080424